

# **2Data i3** Lightweight smart terminal Innovative portability, empower unconnected workers

Nowadays, PDA works not only in warehousing, logistics industries, but also helps workers in all kinds of industries to boost their efficiency. More and more workers who works in apparel stores, libraries, and convenient stores, are able to connect to the digital world by a small portable device, their productivity would eventually benefit from the interconnection.

#### Innovative portability makes the operation more comfortable

Only 178g in weight, i3 has developed its portability as a keyboard/touch control smart terminal to a new lightweight level. The workers who use it to work in fulfillment or inventory won't feel tired after a long time holding by hands, the cylindrical housing design makes it even more comfortable.

#### Small size but versatile for all kinds of business

Small as it is, i3 is a multifunctional device that can scan, take photos and equipped with 4G network, Wi-Fi and Bluetooth. The workers can apply i3 to inventory, order fulfillment, and take photos as proof, etc. Besides, i3 also enables them to talk to each other through voice communication, increasing the collaboration of a whole team.

#### Compact but durable, lower your cost due to malfunction

With the help of IP54 protection and 1.5m anti-drop, i3 can survive many accidental drops, impact, or water splash. The workers can work confidently with i3 in any working environment, and the company won't suffer loss due to malfunction.





Shelving and Removal

cashie

Inbound management

Inventory management

# i3 Technical Specifications

### **System Configuration**

| Processor                       | Quad-core 2.0GHz high-performance processor   |
|---------------------------------|---|
| Operating System                | Android 10.0/Android 11.0   |
| Memory (ROM+RAM)                | 16GB + 2GB (standard), 32GB+3GB/64GB+4GB(optional)  |
| SIM                             | Single SIM card   |
| Display Screen                  | 3.2-inch, resolution: 800*480 pixels  |
| Touch Screen                    | Industrial capacitive screen, support wet-hand operation/glove mode/multi-touch/gesture operation |
| Camera                          | 8 megapixels rear camera(optional 13 megapixels), support auto-focus                              |
| Flashlight                      | 800mA flashlight  |
| Keypad                          | 24 keypads in total: front scan key *21, side scan key *2, side power key *1                      |
| Battery                         | 3.85V lithium battery, with 3000mAh, undetachable   |
| Audio                           | Built-in microphone   |
| Charging Method                 | Type-C charging, support 18W fast charging  |
| Reminder                        | High power speaker reminder/vibration reminder/LED reminder/Audio reminder                        |
| Vibrating Motor                 | Built-in vibrating motor  |
| Sensors                         | G-sensor  |
| Intercom Function<br>(Optional) | Support one-button PTT calls  |
|                                 |   |

#### **Structure Parameter**

| Dimension (L*W*D) | 158mm*54mm*18.5mm            |
|-------------------|------------------------------|
| Weight            | 178g (including the battery) |

#### **Environmental Parameter**

| Working<br>Temperature | -20°C - 60°C *Do not charge under low temperature conditions for the safety Concerns |
|------------------------|--|
| Storage<br>Temperature | -40°C - 70°C (without the battery)   |
| Humidity               | 0 - 95% (no moisture condensation)   |
| Drop Specification     | Multiple drops to concrete floor from the height of 1.5m                             |
| Ingress Protection     | IP54   |
| ESD Protection         | ±15KV (air discharge), ±8KV (contact discharge)                                      |

### **Communication Interface**

| USB Interface | Type-C (with headset function) *1 |
|---------------|-----------------------------------|
| OTG Interface | Support                           |

### **Scanning Engine**

| Barcode Type           | It can scan one-dimensional / twodimensional barcodes |
|------------------------|---|
| Scanning Accuracy      | ≧3.33mil  |
| Scanning Angle         | Pitch: ±60°; Skew: ±45°; Tilt: 360°                   |
| View Angle             | Horizontal: 44.3°, Vertical: 28.4°, Diagonal: 51°     |
| Motion Error Tolerance | 8m/s  |

### **Communication Transmission**

| WWAN<br>(Network Frequency) | China & Eurasian version<br>2G: B2/B3/B5/B8<br>3G: WCDMA: B1/B5/B8, CDMA&EVDO: BC0, TD-SCDMA:<br>B34/B39<br>4G: FDD-LTE: B1/B3/B5/B7/B8/B20, TDD-LTE:<br>B34/B38/B39/B40/B41<br>American version<br>2G: B2/B3/B5<br>3G: B1/B2/B4/B5<br>4G: B1/B2/B3/B4/B5/B7/B12/B17/B28A/B28B/B41 |
|-----------------------------|--|
| WWAN<br>(Data Service)      | GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/EVDO<br>/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE   |
| WLAN Function               | Wi-Fi 802.11a/b/g/n/r/ac (2.4G + 5G dual-band Wi-Fi), support<br>Wi-Fi 5G PA amplifier, fast roaming   |
| Bluetooth                   | Bluetooth 5.0, support BLE   |
| GPS                         | GPS/AGPS/BDS/Galileo/GLONASS/QZSS  |

## NFC (Optional)

| Working Frequency         | 13.56 MHz              |
|---------------------------|------------------------|
| Reading Distance          | Within 60 mm           |
| Communication<br>Protocol | ISO14443A/14443B/15693 |

### **Development Support**

| Programming<br>Language | Java  |
|-------------------------|---|
| Development API         | iScan API (Scanning Development Kits),<br>Device API (Device Management/Configuration Development<br>Kits),<br>Android Standard Interface |
| Development Tool        | Eclipse/Android Studio  |

#### Accessories (More details in accessories guide)

| Standard Accessories | USB cable*1, hand strap *1, power adapter*1 |
|----------------------|---|
| Optional Accessories | Fanny pack, protective case                 |

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



## WUXI IDATA TECHNOLOGY COMPANY LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center, No.999 Gaolang East Road, Wuxi City,Jiangsu Province ,P.R.C. E-mail: sales@idataglobal.com Website: www.idataglobal.com

Official Website

# i3 Standard Accessories

# Each product comes with a pack of practical and cost-effective accessories

# **USB** Cable

Type-C to USB cable, 1m in length, support charging and data transmission



# Hand Strap

Wear on your wrist to carry the device, avoid accidental drops, and assure the safety of equipment



MNT-HS-i3

CHA-USBC-GNR

# **Power Adapter**

Input voltage 100-240V, output 5V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR

ps: you may have one of the power adapters



CHA-PWAD-GNR-5V2A-CN



CHA-PWAD-GNR-5V2A-EU



CHA-PWAD-GNR-5V2A-UK



CHA-PWAD-GNR-5V2A-US




CHA-PWAD-GNR-5V2A-AU

# i3 Optional Accessories for Portability

Accessories Guide

# Improve device portability and comfort for users, boost working efficiency



# i3 Optional Accessories for Protection

# Lower risks of malfunction during usage, extend lifespan of devices

## **Protective Case**

PRT-PTC-i3

Protective case for the main unit. It can prevent the malfunction of main unit in case there's any accidental drops or impact during usage



The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



## WUXI IDATA TECHNOLOGY COMPANY LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center, No.999 Gaolang East Road, Wuxi City,Jiangsu Province ,P.R.C. E-mail: sales@idataglobal.com Website: www.idataglobal.com