



# iData T2HC New-generation Medical Terminal

## Achieving better nursing service

With the help of new generation of 4G medical terminals, real-time interconnection among patients, doctors, and nursing staff can be realized. The 4G networks can be used to upload/query patient information, and remote consultations can have medical teams achieve better nursing service.

### **New-generation 4G network enables faster connection between patients and medics**

The 4G network allows medical workers to upload/query patients' conditions in real time, use efficient networks to quickly start remote consultations, and make nursing plans in time to provide guarantees for improving patients' conditions.

### **Larger touch control screen and HD camera to record and review patient information**

The 6.21-inch HD large screen can display more patient information. The rear 16 million camera can clearly record every detail of the patient's condition, providing a reliable basis for the medical team to make nursing plans.

### **Powerful performance to meet nursing needs in the present and the future**

With the great support of CPU, memory or Android version, the device can not only meet current nursing needs, but also survive longer product circle to face future challenges.



Admission management



SPD material management



Drug traceability



Medical waste Management

# T2HC (4G) Technical Specifications

## System Configuration

Processor	Octa-core 2.0GHz high-performance processor
Operating System	Android 12.0 GMS
Memory (ROM + RAM)	64GB + 4GB
SIM	Two out of three SIM card slots, support dual SIM and dual standby * Two out of three SIM card slots: two cards can be held at the same time, Nano SIM card + Nano SIM card /Nano SIM card +TF card
Expansion Slot	Micro SD card (up to 256 GB)
Display Screen	6.21-inch, resolution: 1520*720 pixels
Touch Screen	Industrial capacitive screen, support wet-hand operation/glove mode/multi-touch/gesture operation
Camera	16MP rear camera + 0.3MP subcamera, support auto-focus/PDAF, 5MP front camera
Flashlight	800mA flashlight
Keypad	5 keypads: side scan key *2, side power key *1, side volume ± key *2
Battery	3.85V lithium battery, with 4500mAh, detachable 3.85V lithium battery, with 4200mAh, detachable, support NFC
Audio	Built-in microphone
Charging Method	Type-C charging and pin port charging, support fast charging of 18W
Reminder	Vibration reminder/LED reminder/high power speaker/Audio reminder
Vibrating Motor	Built-in vibrating motor
Fingerprint Recognition	Support back fingerprint recognition
Sensors	G-sensor/Proximity sensor/Light sensor/Geomagnetic sensor/ Gyroscope
Intercom Function (Optional)	Support one-button PTT calls

## Structure Parameter

Dimension (L*W*D)	168mm*79mm*13.7mm
Weight	245g (including the battery)

## Environmental Parameter

Working Temperature	-20°C - 60°C *Do not charge under low temperature conditions for the safety concerns
Storage Temperature	-40°C - 70°C (without the battery)
Humidity	0 - 95% (no moisture condensation)
Drop Specification	Multiple drops to concrete floor from the height of 1.5m
Roller Drop Specification	1000 times of roller drops from a height of 0.5 meter
Ingress Protection	IP67
ESD Protection	±15KV (air discharge), ±8KV (contact discharge)

## Communication Interface

USB Interface	Type-C (with headset function) *1
OTG Interface	Support

## Scanning Engine

Barcode Type	It can scan one-dimensional / two-dimensional barcodes
Scanning Accuracy	≥3.33mil
Scanning Angle	Pitch: ±60°; Skew: ±45°; Tilt: 360°
View Angle	Horizontal: 44.3°, Vertical: 28.4°, Diagonal: 51°
Motion Error Tolerance	8m/s

## Communication Transmission

WWAN (Network Frequency)	China & Eurasian version: 2G: B2/B3/B5/B8 3G: WCDMA: B1/B5/B8, CDMA&EVDO: BC0, TD-SCDMA: B34/B39 4G: FDD-LTE: B1/B3/B5/B7/B8/B20, TDD-LTE: B34/B38/B39/B40/B41 American version: 2G: B2/B3/B5 3G: B1/B2/B4/B5, CDMA&EVDO: BC0/BC1 (U.S.) 4G: B1/B2/B3/B4/B5/B7/B12/B17/B28A/B28B/B41
WWAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/EVDO /WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
WLAN Function	Wi-Fi 802.11a/b/g/n/ac/d/e/h/i/j/k/r/v/w (2.4G + 5G dual-band Wi-Fi), support fast roaming
Bluetooth	Bluetooth 5.0
GPS	GPS/AGPS/BDS/Galileo/GLONASS/QZSS/GNSS

## NFC (Optional)

Working Frequency	13.56 MHz
Reading Distance	Within 60 mm
Communication Protocol	ISO14443A/14443B/15693

## Development Support

Programming Language	Java
Development API	iScan API (Scanning Development Kits), Device API (Device Management/Configuration Development Kits), Android Standard Interface
Development Tool	Eclipse/Android Studio

## Accessories

Standard Accessories	USB cable*1, power adapter*1, device-back strap*1, battery*1
Optional Accessories	Single charging cradle, bottom charger, 4-slot charging cradle, 4-slot battery charging cradle, fanny pack, protective film, hand strap*1

Each product comes with a pack of practical and cost-effective accessories

## USB Cable

Type-C to USB cable, 1m in length, support charging and data transmission



CHA-USBC-GNR

## Battery

4000mAh, detachable design.

4200mAh, detachable design, support NFC

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-T2-4000MA/4200MA

## Device-back Strap

Attach on the device back to help you hold the device easily and firmly, avoid accidental drops



MNT-BS-T2

## Power Adapter

Input voltage 100-240V, output 5V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR

ps: you may have one of the power adapters



CHA-PWAD-GNR-5V2A-CN



CHA-PWAD-GNR-5V2A-EU



CHA-PWAD-GNR-5V2A-UK



CHA-PWAD-GNR-5V2A-US



CHA-PWAD-GNR-5V2A-AU

## Improve management efficiency of devices and operational level of enterprises

### Bottom Charger

Bottom charger for the main unit, support charging for 1 device. USB-A port, can connect with CHA-PWAD-GNR-5V2A-XX accessory



CHA-BTC-T2

### Battery

4000mAh, detachable design.

4200mAh, detachable design, support NFC

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-T2-4000MA/4200MA

### Single Charging Cradle

Support charging for 1 main unit. Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD1S-T2

### 4-slot Charging Cradle

Support maximum charging of 4 main units at the same time.

Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4S-T2

### 4-slot Battery Charging Cradle

Support maximum charging of 4 batteries at the same time. Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4B-T2

### Improve device portability and comfort for users, boost working efficiency

#### Fanny Pack

Used to carry main units and other accessories. Can be tied to the waist or used as a crossbody bag



MNT-FP-GNR

#### Hand Strap

Wear on your wrist to carry the device, avoid accidental drops, and assure the safety of equipment



MNT-HS-GNR

### Lower risks of malfunction during usage, extend lifespan of devices

#### Protective Film

Protective film for touchscreen. It can protect the screen from cracking or being scratched in case there's any accidental drops or impact during usage



PRT-PTF-T2

The information of iData products and software service may be subject to change without notice. Please contact your iData sales representative for the latest details.



Official Website

#### WUXI IDATA TECHNOLOGY COMPANY LTD.

Address: Floor 11, Building B1, Wuxi (Binhu) National Sensing Information Center,  
No.999 Gaolang East Road, Wuxi City, Jiangsu Province, P.R.C.

E-mail: [sales@idataglobal.com](mailto:sales@idataglobal.com)

Website: [www.idataglobal.com](http://www.idataglobal.com)